

CHARACTER:

1.Physical performance

- a、Excellent mechanical properties
- b、Excellent thermal stability
- c、Low temperature soft good performance
- d、Good flame retardancy
- e、high of resistance to chemicals
- f、Chemistry stability is good

2.Electrical Properties

- a、Electrical insulation good
- b、Good the dielectric properties

3.Processing properties

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、According to UL standard design

4.Environmental protection

- a、low smoke, non-halogen
- b、ROHS/REACH compliant

SHOULD BE USED:

Internal Wiring of Heat Pumps and Refrigerating Equipment.

REFERENCE:

UL758-2010、UL1581-2009

Outline:

Strands Tinned/Bare Copper

XLPE Insulation Jacket

Internal Wiring of Heat Pumps and Refrigerating Equipment. UL3290

Wire structure description:
Conductor: Tinned /Bare copper ;
Insulation materials: XLPE Insulation

Internal wiring 。 Conductor temperature not over125℃ XLPE insulated wire Rated temperature: 125℃ rated voltage: 600V								
STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20℃ (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Nom.	Tole.
3290	10	105/0.254	3.54	3.00	1.52	1.37	6.05	±0.15
	12	65/0.254	5.64	2.36	1.52	1.37	5.40	±0.15
	14	41/0.254	8.96	1.88	1.52	1.37	4.95	±0.15
	16	26/0.254	14.60	1.50	1.52	1.37	4.54	±0.10
	18	16/0.254	23.20	1.17	1.52	1.37	4.20	±0.10
	20	21/0.18	36.70	0.95	1.52	1.37	4.00	±0.10
	22	17/0.16	59.40	0.76	1.52	1.37	3.80	±0.10
	24	11/0.16	94.20	0.61	1.52	1.37	3.65	±0.10
	26	7/0.16	150.00	0.48	1.52	1.37	3.52	±0.10

Marking: E211048 AWM STYLE 3290 NO.AWG 125℃ 600V XLPE QIFURUI AWM I A 125℃ 600V FT2 -LF-
OR: E211048 AWM STYLE 3290 NO. AWG 125℃ 600V XLPE QIFURUI 221756 CSA AWM I A 125℃ 600V FT2 -LF-

SAE COLOR SERIES

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

PACKAGE

*PACKAGE				
Part No.	Packing- FT/roll			
10AWG	□ 200Ft	■ 500Ft	□ 1000Ft	□ 2000Ft
12~16AWG	□ 200Ft	□ 500Ft	■ 1000Ft	□ 2000Ft
18~26AWG	□ 200Ft	□ 500Ft	□ 1000Ft	■ 2000Ft
According to customer requirements for packaging packaging				